Table 1
Information requirements for gaseous/liquid fuel local space heaters

Model identifier(s):	PI2	27 Flueless Gas Fi	re				
Indirect heating functionalit	:y: [y€	≅ /no]					
Direct heat output:	2.1	L (kW)					
Indirect heat output:	N.,	Α.					
Fuel					Space h		missions(*)
						NO _x	
Select fuel type		[gaseous/liquid]				[mg/kWh _{input}] (GCV)	
		Gaseous	Natural Gas		< 130 t.b.c.		
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Heat output				Useful efficiency (NCV)			
Nominal heat output	P _{nom}	2.1	kW	Useful efficiency at nominal heat output	$\eta_{\it th,nom}$	100	%
Minimum heat output (indicative)	P _{min}	1.2	kW	Useful efficiency at minimum heat output (indicative)	$oldsymbol{\eta}_{th,min}$	100	%
Auxiliary electricity consumption				Type of heat output/room temperature control (select one)			
At nominal heat output	el _{max}	0.0	kW	single stage heat output, no room temperature [yes , control			[yes /no]
At minimum heat output	el _{min}	0.0	kW	two or more manual stages, no room [temperature control			[yes/ no]
In standby mode	elsB	0.0	kW	with mechanic thermostat roo control	om temperature [yes /		
				with electronic room tempera			[yes /no]
				with electronic room tempera day timer	·		[yes /no]
				with electronic room tempera week timer	·		[yes /no]
				Other control options (mul	ltiple selections possible)		
				room temperature control, wi	th presence	[yes /no]	
				room temperature control, wi	th open window [[yes /no]
				with distance control option			[yes /no]
				with adaptive start control			[yes /no]
				with working time limitation with black bulb sensor			[yes /no]
Permanent nilet flame n	OWOL ECC.	iromont		with black bulb sensor			[yes /no]
Permanent pilot flame power requirement							
Pilot flame power requirement (if applicable)	P _{pilot}	N.A.	kW				
Contact details	Superior Fires 10 Avon Trading Park, Christchurch, Dorset, BH23 2BT						
(*) NO _x =nitrogen oxides							