Table 1
Information requirements for gaseous/liquid fuel local space heaters

Model identifier(s):	L3!	5 Flueless Stoves					
Indirect heating functionali	ty: [y €	¥s/no]					
Direct heat output:	2.8	3 (kW)					
Indirect heat output:	N.	۹.					
Fuel				Space h		nissions(*)	
		T			NO _x		
Select fuel type		[gaseous/liquid]			[mg/kWh _{input}] (GCV)		
	Gaseous	Natural Gas		< 130 t.b.c.			
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Heat output				Useful efficiency (NCV)			•
Nominal heat output	P _{nom}	2.8	kW	Useful efficiency at nominal heat output	$\eta_{\it th,nom}$	100	%
Minimum heat output (indicative)	P_{min}	1.4	kW	Useful efficiency at minimum heat output (indicative)	$\eta_{\it th,min}$	100	%
Auxiliary electricity consumption				Type of heat output/room temperature control (select one)			
At nominal heat output	el _{max}	0.0	kW	single stage heat output, no room temperature control			[yes /no]
At minimum heat output	el _{min}	0.0	kW	two or more manual stages, no room [stemperature control			[yes/ no]
In standby mode	el _{SB}	0.0	kW	with mechanic thermostat roc control	m tempera	[yes /no]	
				with electronic room tempera			[yes /no]
				with electronic room tempera day timer			[yes /no]
				with electronic room tempera week timer	ture contro	[yes /no]	
				Other control options (mul	her control options (multiple selections possible)		
				room temperature control, wi	perature control, with presence		
				room temperature control, wi	th open wir	[yes /no]	
				with distance control option	on		[yes /no]
				with adaptive start control			[yes /no]
				with working time limitation			[yes /no]
Dawnson and will at flower		·iua ua a uat		with black bulb sensor			[yes /no]
Permanent pilot flame p	-	1	1				
Pilot flame power requirement (if applicable)	P _{pilot}	N.A.	kW				
Contact details		Focal Point Fires Plc. 10 Avon Trading Park, Christchurch, Dorset, BH23 2BT					
(*) NO _x =nitrogen oxides							